Fast Dry

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 8/18/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Fast Dry
Vaporizer : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Texture spray for patching
Restrictions on use : Keep away from open flame

1.4. Supplier's details

Texturetek LLC
3020 Red Hill Ave
Costa Mesa, CA 92626
T 714-248-8797
sales@texturetek.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 866912
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.
Specific target organ toxicity — Repeated exposure, Category 1	H372	Causes damage to organs (blood, kidneys, liver, lungs, heart) through prolonged or repeated exposure (if inhaled).

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H222 - Extremely flammable aerosol
H229 - Pressurized container; may burst if heated
H351 - Suspected of causing cancer.
H360 - May damage fertility or the unborn child

		H372 - Causes damage to organs (blood, kidneys, liver, lungs, heart) through prolonged or repeated exposure (if inhaled)
Precautionary statements (GHS US)	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist, spray, vapors. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye and face protection. Get medical advice or attention if you feel unwell. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Limestone	CAS-No.: 1317-65-3	50.854	Not classified
Dimethyl ether	CAS-No.: 115-10-6	10.2	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Mica	CAS-No.: 12001-26-2	4.355	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 1, H372
Ethanol	CAS-No.: 64-17-5	2.712	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Attapulgite	CAS-No.: 12174-11-7	0.754	Carc. 2, H351
Titanium dioxide	CAS-No.: 13463-67-7	0.26	Carc. 2, H351
Disodium octaborate	CAS-No.: 12280-03-4	0.18	Repr. 1B, H360

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but, not mouth-to-mouth. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious: Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Causes damage to organs (kidneys, lungs, blood, liver) through prolonged or repeated exposure (inhalation).

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs (blood, heart, liver, kidneys, lungs) through prolonged or repeated exposure (inhalation).

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : IF exposed or concerned: Get medical advice/attention. If inhaled, remove to fresh air. If necessary, supply oxygen.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray. Dry powder.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Reactivity in case of fire : Toxic and corrosive vapors may be released.

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Do not enter fire area without proper protective equipment, including respiratory protection. Fight fire from safe distance and protected location. Eliminate all ignition sources if safe to do so. Small fires: Do not extinguish a leaking gas flame unless absolutely necessary. Contain and let burn. If fire must be fought, water spray or fog is recommended. Move containers from fire area if it can be done without personal risk. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. ALWAYS stay away from tanks engulfed in fire. Prevent fire-fighting water from entering environment.

Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	:	Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Do not breathe gas, fume, vapors. If possible without taking personal risks, Remove ignition sources, ventilate area. Monitor concentration of released product. Prevent other non-emergency personnel from entering the danger area. Only qualified personnel equipped with suitable protective equipment may intervene.

For emergency responders

Protective equipment	:	Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Environmental precautions	:	Avoid release to the environment. Notify authorities if the product reaches soil, drains, sewers, surface waters or groundwater.

6.2. Methods and materials for containment and cleaning up

For containment	:	Absorb spilled material with sand or earth. Stop leak, if possible without risk. For large spills, use water spray to disperse vapors, flush spill area.
Methods for cleaning up	:	Ventilate spillage area. Do not touch or walk on the spilled product.
Other information	:	Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

For further information refer to section 8: "Exposure controls/personal protection",For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Do not breathe fume, gas, vapors. Wear protective gloves, protective clothing, eye protection, face protection. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing.
Hygiene measures	:	Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.
Additional hazards when processed	:	Containers should be stored in the vertical position and properly secured to prevent toppling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Use self-contained breathing apparatus and chemically protective clothing.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	:	Always keep container in upright position. Do not expose to temperatures exceeding 50 °C / 122 °F. Protect from sunlight. Store in a well-ventilated place. Keep cool.
Incompatible materials	:	Strong oxidizing agents.
Heat-ignition	:	Keep away from sources of ignition - No smoking.
Packaging materials	:	Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Limestone (1317-65-3)	
USA - OSHA - Occupational Exposure Limits	
Local name	Calcium Carbonate (Limestone; Marble)
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Calcium Carbonate (Limestone; Marble)
NIOSH REL 10h TWA	10 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Mica (12001-26-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Mica
ACGIH® TLV® TWA	0.1 mg/m³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Mica (Silicates (less than 1% crystalline silica))
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - NIOSH - Occupational Exposure Limits	
Local name	Mica (Silicates (less than 1% crystalline silica))
NIOSH REL 10h TWA	3 mg/m³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-3 Mineral Dusts (NIOSH Pocket Guide to Chemical Hazards (NPG))

Titanium dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide

Titanium dioxide (13463-67-7)	
ACGIH® TLV® TWA	0.2 mg/m³ (Nanoscale particles. R - Repirable particulate matter) 2.5 mg/m³ (Finescale particles. R - Repirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
NIOSH REL 10h TWA	2.4 mg/m³ (fine) 0.3 mg/m³ (ultrafine)
Remark (NIOSH)	Ca = Potential occupational carcinogens (ultrafine particles)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Ethanol (64-17-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanol
ACGIH® TLV® STEL	1880 mg/m³
	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OSHA PEL TWA	1900 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
NIOSH REL 10h TWA	1000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Materials for protective clothing:
Flame retardant antistatic protective clothing

Hand protection:
Protective gloves. Chemically impervious gloves as described by OSHA's hand protection regulations in 29 CFR 1910.138

Eye protection:
Chemical goggles or safety glasses. Wear safety glasses which protect from splashes

Skin and body protection:
Wear suitable protective clothing. Chemical-resistant safety shoes

Respiratory protection:
In case of inadequate ventilation wear respiratory protection. Self-contained breathing apparatus

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Paste. Slurry.
Color	:	Off-white
Odor	:	Mild
Odor threshold	:	No data available
pH	:	8.6 – 8.7
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Density	:	13.95 lb/gal
Solubility	:	Soluble.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	17947.107 mm²/s
Viscosity, dynamic	:	30000 cP @ 22.22 °C / 72 °F
Explosion limits	:	No data available
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Chemical under pressure: May explode if heated.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces, heat, flames, and sparks. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Dimethyl ether	
LC50 Inhalation - Rat	308.5 mg/l
LC50 Inhalation - Rat [ppm]	164000 ppm

Titanium dioxide	
LD50 oral rat	> 5000 mg/kg body weight

Disodium octaborate	
LD50 oral rat	> 2550 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Ethanol	
LD50 oral rat	7060 mg/kg body weight
LD50 oral	6200 mg/kg
LD50 dermal rabbit	> 18000 mg/kg body weight
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	124.7 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 8.6 – 8.7

Ethanol	
Skin corrosion/irritation, rabbit	Not irritating to rabbits on cutaneous application

Serious eye damage/irritation : Not classified
pH: 8.6 – 8.7

Ethanol	
Serious eye damage/irritation, rabbit	Moderately irritating

Respiratory or skin sensitization : Not classified

Ethanol	
Skin sensitization, mouse	Not sensitive

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Attapulgite	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable

Titanium dioxide	
IARC group	2B - Possibly carcinogenic to humans

Ethanol	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not classified

Mica	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Causes damage to organs (blood, kidneys, liver, lungs, heart) through prolonged or repeated exposure (if inhaled).

Mica	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Ethanol	
NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight

Aspiration hazard : Not classified

Fast Dry	
Vaporizer	Aerosol
Viscosity, kinematic	17947.107 mm²/s

Symptoms/effects after inhalation : Causes damage to organs (kidneys, lungs, blood, liver) through prolonged or repeated exposure (inhalation).

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms : Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs (blood, heart, liver, kidneys, lungs) through prolonged or repeated exposure (inhalation).

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

Dimethyl ether	
LC50 - Fish [1]	> 4.1 g/l
EC50 - Crustacea [1]	> 4.4 g/l
EC50 96h - Algae [1]	154917 mg/l
ErC50 algae	155 mg/l

Titanium dioxide	
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
LOEC (chronic)	5 mg/l

Ethanol	
LC50 - Fish [1]	11200 mg/l
EC50 - Crustacea [1]	5463 mg/l
ErC50 algae	1000 mg/l
NOEC (chronic)	9.6 mg/l
NOEC chronic crustacea	9.6 mg/l

12.2. Persistence and degradability

Fast Dry	
Persistence and degradability	Not established.

Dimethyl ether	
Persistence and degradability	Not rapidly degradable

Limestone	
Persistence and degradability	Not rapidly degradable

Mica	
Persistence and degradability	Not rapidly degradable

Attapulgite	
Persistence and degradability	Not rapidly degradable

Titanium dioxide	
Persistence and degradability	Not rapidly degradable

Disodium octaborate	
Persistence and degradability	Not rapidly degradable

Ethanol	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Dimethyl ether	
Partition coefficient n-octanol/water (Log Pow)	0.1

12.4. Mobility in soil

Dimethyl ether	
Mobility in soil	27

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : U.S. - RCRA (Resource Conservation Recovery Act) - D Waste- Characteristic Waste Codes. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions. D001: IGNITABLE WASTE.
Additional information : Do not re-use empty containers.
Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols, flammable, n.o.s.	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
14.4. Packing group		
Not applicable	Not applicable	Not applicable

DOT	IMDG	IATA
14.5. Environmental hazards		
	Dangerous for the environment: No Marine pollutant: No	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT)	:	UN1950
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	304
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	:	25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
ERG code (IATA)	:	10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Mica	CAS-No. 12001-26-2	4.355%

Attapulgite	CAS-No. 12174-11-7	0.754%
Disodium octaborate	CAS-No. 12280-03-4	0.18%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Dimethyl ether (115-10-6)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Mica (12001-26-2)

Listed on the Canadian DSL (Domestic Substances List)

Attapulgite (12174-11-7)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Titanium dioxide

Listed on the Canadian DSL (Domestic Substances List)

Disodium octaborate (12280-03-4)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Dimethyl ether (115-10-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Limestone (1317-65-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Mica (12001-26-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Attapulgite (12174-11-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Titanium dioxide

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

WARNING: This product can expose you to Palygorskite fibers (> 5µm in length), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Dimethyl ether(115-10-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Limestone(1317-65-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Mica(12001-26-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethanol(64-17-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date : 8/18/2025

Full text of hazard classes and H-statements	
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation

Full text of hazard classes and H-statements	
H335	May cause respiratory irritation
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.